

Calore 200W/m² Underfloor Heating Mat – 7m²




Product Specifications

Code: CAL-FHM20-7M


Barcode: 9339897010580

Primary Material: N/A

Technical Features: 240VAC Hardwire Only
Included: CAL-SCR-M Alarm



| SIZE (M2) | LENGTH | WIDTH | WATTAGE | AMPS | RESISTANCE RANGE |
|-----------|--------|-------|---------|------|------------------|
| 1.0 | 2.0 m | 0.5 m | 200 W | 0.8 | 259-317 Ω |
| 1.5 | 3.0 m | 0.5 m | 300 W | 1.2 | 173-211 Ω |
| 2.0 | 4.0 m | 0.5 m | 400 W | 1.7 | 130-158 Ω |
| 2.5 | 5.0 m | 0.5 m | 500 W | 2.1 | 103-126 Ω |
| 3.0 | 6.0 m | 0.5 m | 600 W | 2.5 | 86-106 Ω |
| 3.5 | 7.0 m | 0.5 m | 700W | 2.9 | 82.2-95 Ω |
| 4.0 | 8.0 m | 0.5 m | 800 W | 3.3 | 65-79 Ω |
| 4.5 | 9.0 m | 0.5 m | 900 W | 3.8 | 56-66 Ω |
| 5.0 | 10.0 m | 0.5 m | 1000 W | 4.2 | 52-63 Ω |
| 6.0 | 12.0 m | 0.5 m | 1200 W | 5 | 43-53 Ω |
| 7.0 | 14.0 m | 0.5 m | 1400 W | 5.8 | 37-45 Ω |
| 8.0 | 16.0 m | 0.5 m | 1600 W | 6.7 | 32-40 Ω |
| 9.0 | 18.0 m | 0.5 m | 1800 W | 7.5 | 29-35 Ω |
| 10.0 | 20.0 m | 0.5 m | 2000 W | 8.3 | 26-32 Ω |
| 11.0 | 22.0 m | 0.5 m | 2200 W | 9.2 | 23-29 Ω |
| 12.0 | 24.0 m | 0.5 m | 2400 W | 10.0 | 22-26 Ω |
| 14.0 | 28.0 m | 0.5 m | 2800 W | 11.6 | 19-20.6 Ω |
| 16.0 | 32.0 m | 0.5 m | 3200 W | 13.3 | 18-20 Ω |



Experience, *the difference.*



LINSOL.COM.AU

☎ 1300 546 765

✉ info@linsol.com.au

✉ PO Box 88, Coniston NSW 2500

All information is correct at time of writing. The actual product may vary slightly and sizes may be scaled up or down. Warranty is for domestic use only. For warranty & care information please visit linsol.com.au/warranty